



MACHINE CONSTRUCTION

AGRICULTURE IRRIGATION EARTH MOVING

AP IRRIGATION MACHINES TURBINE DRIVEN



Quality machines



Made in Holland



Standard equipment AP irrigation machine turbine driven



Drive

Gearbox with 4 gears. Turbine with integrated bypass valve.

Support legs by tractor hydraulics

Automatic picking-up gun cart

At the end of each draft the gun cart can be lifted by the tractor hydraulics, so that the irrigation machine can be moved immediately.

2-Track adjustable gun cart / sled - Width and angle adjustment

Due to the unique cannon car the risk of crop damage is minimal. Track width 1.50 to 2.25 m.

Sprinkler

Nelson SR 150 with 3 nozzles.

Automatic idle function

While pulling out the hose this is idling, which means the pulling out takes less power.

Automatic controlled drum brake

Enters into force during the pulling out, to prevent loose windings.

Turntable

Wheel bearing supported turntable, free of maintenance, to smoothly adjust the spraying direction (per 7 degrees).

Quick winding system through tractor PTO

By the tractor PTO the gun cart / sled can be entered without irrigating, during rain or when otherwise desirable. **Exclusive of PTO.**

Security of the irrigation machine

The irrigation machine is protected on winding errors and the end of the draft. When a computer is mounted the machine is also protected when the machine stops rolling.

Type	Ø Hose mm	Length hose m
T1	100	350, 400
T1	110	300, 320
T2	110	450, 500, 550
T2	125	350, 400, 440
T3	110	550, 600, 650
T3	125	500, 550